



### **Premier Track**

Protect internal flooring with heavy-duty, premium quality entrance tiles















- Effectively removes moisture and debris, even from wheeled trolleys, without buckling.
- Safe for high heeled footwear, heels won't get stuck in the tiles.
- Move, clean or replace individual tiles they clip together with ease.
- Easily cut to shape, so you can fit to any space and install faster with fewer specialist tools.
- Exceptionally durable carpet inserts manufactured from ECONYL<sup>®</sup>, a recycled nylon material made from discarded fishing nets and other sources.
- Ideal for recessed entrance wells.
- Fire tested to BS EN 13501-1 and slip tested to BS 7676-2.



#### **Styles Available**





Blue





Grey

Anthracite

#### **Parts**

Brown

| Part Number | Size          | Colour     | Weight  |
|-------------|---------------|------------|---------|
| PT010101    | 29 cm x 44 cm | Anthracite | 1.20 kg |
| PT010201    | 29 cm x 44 cm | Blue       | 1.20 kg |
| PT010501    | 29 cm x 44 cm | Brown      | 1.20 kg |
| PT010601    | 29 cm x 44 cm | Grey       | 1.10 kg |
| PT010101C   | 29 cm x 44 cm | Anthracite | 1.20 kg |
| PT010201C   | 29 cm x 44 cm | Blue       | 1.20 kg |
| PT010501C   | 29 cm x 44 cm | Brown      | 1.20 kg |
| PT010601C   | 29 cm x 44 cm | Grey       | 1.10 kg |

## **Technical Specification**

| Material                | ECONYL® Regenerated Nylon in PVC tile |
|-------------------------|---------------------------------------|
| Product<br>Height       | 16 mm                                 |
| Typical<br>Applications | Entrance areas                        |
| Installation<br>Method  | Installed in to recessed well         |
| Fire Tested to          | BS EN 13501-1 Class Cfl - s2          |
| Country of Origin       | UK                                    |
| Guarantee               | 5 years                               |

# **Technical Specification**

Notes

Alba is a tufted carpet product and therefore its appearance can vary depending on the direction of the pile and the light in the surrounding environment. To achieve a uniform appearance consider hoovering the product in a single direction.

Slip Tested

to

BS 7676-2 - low slip potential

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com