

## Double Sided Tape

High strength double sided tape ideal for Superdry Heavy Traffic



- High performance double-sided filmic bonding tape
- Achieve a tougher, thinner, weather resistant bond.
- A tough polyester carrier forms the base for a very strong, high shear solvent acrylic adhesive.
- UV, temperature and moisture stable.

## Parts

Part Number	Size	Colour	Weight (kg)
DST0001	50 mm x 50 m	Clear	

## Technical Specifications

Product Height	0.215mm – 0.225mm
Min. Operating Temperature	20°C
Max. Operating Temperature	+80°C
COO (Country of Origin)	UK
Storage and application	This product should be stored in ambient temperatures of around 20°C, avoiding wide temperature fluctuations and direct sunlight. The storage environment should have a relative humidity of approx. 50%. In ideal storage conditions, the shelf life for this material should be approx. 12 months from the delivery date. Within this period, no major deterioration or alteration of the products performance characteristic will occur. The values presented in this document have been determined by standard test methods and are average values that should not be used for specification purposes without conducting tests on materials to be bonded.

<b>Notes</b>	The surfaces to be bonded should be dry, dust and grease free and thoroughly clean. Avoid touching the exposed adhesive surface of the tape as this impairs the performance. The adhesive used on these tapes are pressure sensitive, so always ensure sufficient pressure is applied to the tape evenly over the whole surface to ensure the best bonding results.
<b>Carrier</b>	23 Micron Transparent Polyester
<b>Adhesive</b>	A cross-linked, solvent acrylic with very high tack. The adhesive has very good cohesive strength and the initial bond although very high, reaches an even higher ultimate bond over 12 – 24 hours.
<b>Liner</b>	Narrow widths up to 100mm: 80μ red OPP siliconized both sides. Widths over 150mm: White 115gsm polyethylene coated paper to facilitate cutting.
<b>Tape Thickness</b>	0.215mm – 0.225mm (230 micron Tape and Adhesive)
<b>Temperature resistance (short-term)</b>	-20°C to + 180°C
<b>Initial Tack</b>	(Side A/B) (PSTC-6 #14 Ball) <5cm
<b>Holding Power</b>	(Side A/B) (PSTC-7) >24hrs 1kg/2.5cmx2.5cm
<b>Holding Power for temperature resistance @ 60°C: (PSTC-7)</b>	> 24 hrs. 0.5kg/2.5cmx2.5cm
<b>Initial Tack: (Side A/B) (PSTC-6 #14 ball)</b>	< 5 cm
<b>Adhesion: (Side A/B) (PSTC-1)</b>	g/15mm >2500. OZ/0.6in >88.19. N/15mm >24.4.

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

[www.cobaeurope.com](http://www.cobaeurope.com)