NONG LADDENS www.nymer-aiu.de



6046 Extension ladder, two-section

- > Inner width of the ladder 300 mm (top section).
- Rungs made of high rib extruded profiles providing increased slip resistance.
- The high-quality steel fittings are equipped with plastic sliders on the inside (to ensure better sliding behaviour of sections).
- With wall rollers to easily extend the ladder from size 2×14 upwards.
- > Size 2×6: **folding aluminium feet** with large bearing surface.
- Arched cross-beam from size 2×8 upwards (125 mm ground clearance).



Number of rungs	2×6	2×8	2×10	2×12	2×14	2×16	2×18
Stile top/bottom (approx. mm)	60/60	60/60	66/66	71/71	83/83	89/89	89/89
Number of rungs at max. extension	10	14	17	21	25	29	32
Length retracted (approx. m)	1.85	2.43	2.99	3.55	4.16	4.72	5.28
Length extended (approx. m)	2.97	4.11	4.95	6.07	7.24	8.36	9.15
Standing height (approx. m)	1.92	3.00	3.81	4.89	5.97	7.05	7.86
Reach height (approx. m)	3.92	5.00	5.81	6.89	7.97	9.05	9.86
Width extended top/bottom (approx. mm)	355/440	355/880	355/880	355/955	355/1,075	355/1,200	355/1,200
Weight (approx. kg)	7.3	9.9	12.0	15.2	18.5	23.2	28.6
Order no.	604612	604616	604620	604624	604628	604632	604636

For an explanation of standing/reach height see on page 5.

Recommended accessories:



Add-on step set for rung ladders



Set of foot pikes for cross-beams



Telescopic wall spacer for rung ladders



Ladder holder set for gutters



Ladder bracket set for roof racks



Retrofit kit telescopic stabilisers