

LIFTMATE ELECTRIC MINI LIFTERS



E100



E150



E250



Features:

- Lightweight and compact design
- Versatile and easy to operate
- Designed with a portable and adjustable hand control unit
- The lifter is a perfect solution for narrow aisles and confined spaces thanks to its overall size
- Lift/lowering system with electrical motor
- Maintenance free, sealed battery
- Electric overload protection
- Automatic brake system ensures a safe lowering
- Supplied with platform and forks as standard
- Non-marking swivel castor wheels - 2 of which are fitted with foot brakes
- The E250 model has 2 fixed wheels on the legs



Technical Specifications:

Model		E100	E150	E250
Capacity	(kg)	100	150	250
Load Centre	(mm)	235	235	200
Min-Max Lift Height	(mm)	130-1700	130-1500	130-1905
Platform Size (LxW)	(mm)	475 x 600	475 x 600	475 x 610
Fork Length	(mm)	400	400	400
Width over Forks	(mm)	330	330	330
Battery	(V/Ah)	24/12	24/12	24/20
Steer/Load Wheels	(mm)	ø125 / ø75	ø125 / ø75	ø125 / ø75
Dimension (LxWxH)	(mm)	850x600x1970	825x600x1780	840x600x2220
Weight	(kg)	66	63	90

Electric Mini Lifter Optional Attachments



Ball Transfer Unit – EP01
610 x 480mm
Capacity: 150kg



Roller Platform – EP02
500 x 420mm
Capacity: 150kg



V Block – EP03
Capacity: 250kg



Single Boom Spindle – EP05
ø50 x 600mm
Capacity: 250kg



Double Spindle – EP06
ø50 x 500mm (260mm centres)
Capacity: 250kg



Jib and Hook – EP07
500mm long
Capacity: 150kg



200mm Raised Frame