

FIRECHIEF LAYFLAT HOSES

FIRECHIEF®
making the world a safer place

MODEL:

LH45/18

LH65/23/2

LH65/23/3

- Layflat hoses conform to respective requirements of BS6391:2009:
Type 2 - LH65/23 and LH45/18
Type 3 - LH65/23/3
- Complete with light alloy instantaneous couplings
- Type 2 is constructed from close woven twill polyester filament yarns with synthetic rubber lining
- Type 3 has a premium nitrile rubber outer jacket
- No drying
- Quick to stow
- Designed for emergency use



LH65/23
103-1088



LH45/18
103-1038



LH65/23/3
103-1089



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

FIRECHIEF LAYFLAT HOSES



Durable hosing:
LH45/18 and LH65/23/2 (Type 2) manufactured from close woven twill polyester filament yarns with synthetic rubber lining.

LH65/23/3 (Type 3) incorporates a premium nitrile rubber outer jacket.

MODEL:

LH45/18

LH65/23/2

LH65/23/3



All hoses supplied with 2.5" instantaneous couplings in aluminium alloy.



Model	LH45/18	LH65/23/2	LH65/23/3
Product Code	103-1038	103-1088	103-1089
Storage Height (approx) (mm)	90	120	100
Storage Diameter (approx) (mm)	380	420	440
Weight (kg)	4.5	14.1	15
Overall length (m)	18.3	23	23
Internal diameter (mm)	45	65	65
Working Pressure (bar)	15	15	15
Burst Pressure (bar)	50	50	50
Unit of Sale	1	1	1

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland

+44 (0) 330 999 0019

sales@firechiefglobal.com

firechiefglobal.com