

Powder

The Premium Range Powder fire extinguisher is made in our UK factory and is available in 2kg, 4kg, 6kg and 9kg ABC powder models. For use on Class A, B and C fires making them suitable for use in environments containing multiple fire risks. They are highly effective against petrol and volatile liquids which makes them ideal for vehicle protection. All models come complete with the distinctive Jactone colour coded handle, header label and base* and are Kitemark certified to BS EN3, UKCA and CE marked.

- Quality deep drawn cylinders*.
- High quality heavy-duty brass valves.
- Colour coded headers, handles and bases*.



MADE IN THE UK



COLOUR CODED



FULLY CERTIFIED



5 YEAR GUARANTEE

*4kg, 6kg and 9kg models only.



➤ EPS2 : 2kg ABC Powder

➤ EPS4 : 4kg ABC Powder

➤ EPS6 : 6kg ABC Powder

➤ EPS9 : 9kg ABC Powder

Product Certification and Specification



KM 57904
BS EN 3

UK
CA
0086

CE
2797



- EXTINGUISHER :
- PRODUCT CODE :
- MEDIUM :
- PROPELLANT :
- FIRE RATING :
- OPERATING TEMPERATURE :
- OPERATING PRESSURE :
- AVERAGE DISCHARGE TIME :
- HEIGHT & DIAMETER :
- FILLED & EMPTY WEIGHTS :
- PACKING SPEC (HxWxD) :

| 2kg ABC Powder | 4kg ABC Powder | 6kg ABC Powder | 9kg ABC Powder |
|-------------------|--------------------|--------------------|--------------------|
| EPS2 | EPS4 | EPS6 | EPS9 |
| ABC 40 Dry Powder | ABC 40 Dry Powder | ABC 40 Dry Powder | ABC 40 Dry Powder |
| Nitrogen gas | Nitrogen gas | Nitrogen gas | Nitrogen gas |
| 13A 70B C | 21A 113B C | 27A 183B C | 43A 233B C |
| -20°C to +60°C | -20°C to +60°C | -20°C to +60°C | -20°C to +60°C |
| 15 bar at 20°C | 15 bar at 20°C | 15 bar at 20°C | 15 bar at 20°C |
| 9.5 seconds | 12.9 seconds | 16.1 seconds | 16.7 seconds |
| H 391mm D 108mm | H 411mm D 160mm | H 517mm D 160mm | H 552mm D 189mm |
| F 3.2kg E 1.2kg | F 6.95kg E 2.9kg | F 9.55kg E 3.5kg | F 13.6kg E 4.5kg |
| 393 x 159 x 117mm | 415 x 175 x 175mm | 529 x 177 x 177mm | 549 x 205 x 205mm |