

SPECIFICATION SHEET

1.8M KERNMANTEL ENERGY ABSORBING LANYARD



Product Code:

MSA10185614

Selling UOM:

Each

Pack Size:

1

The MSA lanyards are available in web and kernmantel rope configurations with a variety of connectors. Energy-absorbing lanyards provide a means of connection between the fall arrest attachment of MSA full body harnesses and a qualified anchorage point. The energy absorber keeps fall arrest forces below 6 kN.

- Single leg configuration, twin-leg options also available
- Leading edge approved for use in leading edge application
- Cross stitch and a strong transparent covering sleeve to protect the ends and makes the stitches visible for easy inspection
- Abrasion resistant thimble at the end of the loops to prevent the rope from being damaged by the metallic contact of the connector
- A colour tracer strand that loses its colour in due course of time showing that the lanyard is now unfit for further use
- 11mm Nylon Kernmantel rope
- Galvanized alloy steel twist-lock carabiner
- The Carabiner has a minimum breaking strength of 23kN with a gate opening of 60mm
- Aluminum Alloy Scaffolding hook
- The Scaffolding hook has a minimum breaking strength of 23 kN with a gate opening of 16 mm
- Maximum arrest force of 6kN
- Conforms to EN 352:2002 Personal protective equipment against falls from a height. Energy absorbers



Packaging Waste

Cardboard

Carton Weight:

22.00kg

Type

Outer

Units

1

Weight(g)

1,350.00

Length(mm)

600.00

Width(mm)

400.00

Height(mm)

240.00

t: 08007999763

