

Brad Nailer LXT®

DBN600RTJ

18V • 25 – 64 mm

Cordless brad nailer for finish work

A hose-free brad nailer. An in-built compressor provides a nailing touch similar to that offered by a pneumatic nailer. Ideal for finish and trim work, including installing panels and trimmings. The nailer is compatible with 1.6 mm nails with a length of 25 – 64mm. Two 5.0Ah batteries and a rapid charger in a Makpac case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Nail Length	25 - 64 mm
Nail Diameter	1,6 mm
Fastener Gauge	16 Ga
Fastener Magazine Capacity	110
Sound Pressure Level (L _{pA})	89 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product net weight	3,2 kg
Tool weight with battery (EPTA)	3,4 - 3,8 kg
Product Dimensions (L x W x H):	296 x 107 x 318 mm
Depth Adjustment	✓

User benefits

- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

EAN 0088381852081

Link to product - www.makitauk.com



Related products

Standard AC

251314-2

Truss Head Screw M4*12, Td140D



346317-0

Belt Hook



424443-6 (2x)

Nose Adapter Af600



450128-8

Battery cover, LXT®, 14,4 – 18V



821552-6

Makpac case (4)



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

251314-2

Truss Head Screw M4*12, Td140D



346317-0

Belt Hook



424443-6

Nose Adapter Af600



450128-8

Battery cover, LXT®, 14,4 – 18V



821552-6

Makpac case (4)



839523-9

MakPac (4) Inlay



Other

[User manual](#)

[Parts drawing](#)